

1080p Transmitter with TVI In, USB, and HDMI Out

The 726TVI Transmitter adds TVI support, HDMI loopout and USB 2.0 to any 2G Omega or 3G Ultra Just Add Power video distribution system.

Add a TVI source to your HD over IP system without the need for an TVI-HDMI converter.

The 726TVI Transmitter encodes a 1080p or lower source device into an IP signal and sends it over the network with ultra-low latency and instant switching; and features image pull and KVM support.




Features

Audio	Line-in for injecting audio	KVM Support	Provide local and remote access to all computers on the system with a built-in keyboard, mouse and touchscreen interface at both ends of a connection
HDMI	HDMI pass-through	Scalability	Fully compatible with all 3G Ultra and 2G Omega products
Image Pull	Preview an image from any source or display in any web browser or control system - up to 10 fps		

2G OMEGA VBS-HDIP-726TVI


Just Add
Power
AV over IP Solutions

Front of Device:



All measurements in millimeters (mm)

Back of Device:



All measurements in millimeters (mm)

Specifications

Bandwidth	180-500 Mbps	POE	IEEE 802.3af (15.4W)
Compliance	RoHS/FCC/CE	Ports	Gigabit Ethernet HD-TVI In HDMI Out 3.5mm Line-In USB 2.0 Type B
Dimensions & Weight	159 x 30 x 124 mm 6.3" x 1.2" x 4.9" inch 0.36 kg / 0.8 lb	Power Supply (not included)	5V-18V 5.5mm/2.1mm, Positive tip
Encryption	AES-128 Encryption	Supported Resolutions	Up to 1080p
Operating Temp	0-60 °C / 32-140 °F		