

# 3G ULTRA VBS-HDIP-518AVP

Just Add  
**Power**  
AV over IP Solutions

## 4K Receiver with USB and Stereo Audio Out

The Just Add Power 3G Ultra 518AVP Receiver distributes 4K video and supports all lossless audio formats over a single Catx cable.

The 518AVP receives and processes a 4K or lower-resolution source from a Just Add Power Transmitter and distributes video to the designated display; supports analog audio output with amp and delay; features integrated endpoint control and KVM support - along with all the 4K Receiver system wide features from the 3G Ultra product line.




### Features

<b>Image Pop</b>	Display a custom logo or message as an overlay on any active screen	<b>Integrated Endpoint Control</b>	Control endpoints with RS232, IR and CEC
<b>Image Push</b>	Load a custom default image or logo for when no source is displayed onscreen	<b>KVM Support</b>	Provide local and remote access to all computers on the system with a built-in keyboard, mouse and touchscreen interface at both ends of a connection.
<b>Image Pull</b>	Preview an image from any source or display in any web browser or control system - up to 10 fps	<b>Video Rotation</b>	Rotate your video by 90° for portrait or landscape display

# 3G ULTRA VBS-HDIP-518AVP


Just Add  
**Power**  
AV over IP Solutions

## Front of Device:



All measurements in millimeters (mm)

## Back of Device:



All measurements in millimeters (mm)

## Specifications

<b>Bandwidth</b>	180-500 Mbps	<b>POE</b>	IEEE 802.3af (15.4W)
<b>Compliance</b>	HDCP 2.2 RoHS/FCC/CE	<b>Ports</b>	USB 2.0 (2x) (front of device)  Gigabit Ethernet HDMI Out 3.5mm Stereo Out 3.5mm RS232 w/null modem
<b>Dimensions &amp; Weight</b>	184 x 30 x 127 mm 7.2" x 1.2" x 5.0" in 0.45 kg / 1.0 lb	<b>Power Supply (not included)</b>	5V-18V 5.5mm/2.1mm, Positive tip
<b>Encryption</b>	AES-128 Encryption	<b>Supported Resolutions</b>	Up to 4096x2160 (interlaced & progressive)
<b>Operating Temp</b>	0-60 °C / 32-140 °F		